


Mitsubishi Electric introduces the R32 MSZ-EF Series, expanding our line-up in the low Global Warming Potential (GWP) refrigerant. With just one third of the GWP of the R410A we aim to help reduce the household carbon footprint. The streamlined wall mounted indoor units have contemporary clean lines, expressing sophistication and quality, and is available in 3 stylish colours.



Quiet Operation

The "Quiet" fan speed setting ensures super quiet operation below 21dB*. Perfect for the bedroom; it's so quiet you'll check to see if it's on.
*Model 25/35 only.



Nano Platinum Filter

The Nano Platinum Deodorising Filter reduces airborne bacteria while improving air quality. The optional Electro Static Anti-Allergy Enzyme Filter assists in the reduction of common allergens.



Backlit Controller

With an easy to read backlit display and a variety of operating modes at the touch of a button. This controller features a weekly and 24 hour timer, On/Off timer to set operating times on a daily basis. The 'i-Save' mode recalls the preset temperature.

Features

- Capacity Range: 2.5/3.5/4.2/5.0kW
- ✔ Unit Dimensions: 895 (w) x 195 (d) x 299mm (h)
- Built-In Weekly Timer
- Quiet 21dB Noise Level in 'Quiet Mode' (EF25/35)
- Nano Platinum Filter
- Appealing design matches any room décor
- ✓ Wi-Fi Control*
- Colour: Natural White, Matte Silver and Glossy Black

Product Specifications

Indoor Unit Outdoor Unit			MSZ-EF25VG (W/B/S) -A1	MSZ-EF35VG (W/B/S) -A1	MSZ-EF42VG (W/B/S) -A1	MSZ-EF50VG (W/B/S) -A
			MUZ-EF25VG-A1	MUZ-EF35VG-A1	MUZ-EF42VG-A1	MUZ-EF50VG-A1
Refrigerant				R	32	
Cooling	Capacity [Rated]	kW	2.50	3.50	4.20	5.00
	Capacity [Min-M	ax] kW	0.90 - 3.40	1.10 - 4.00	0.90 - 4.60	1.40 - 5.40
	Total Input [Rate	d] kW	0.54	0.91	1.20	1.55
	Total Input [Min-	Max] kW	0.23 - 1.15	0.21 - 1.50	0.15 - 1.93	0.30 - 1.98
	EER		4.63	3.85	3.50	3.23
	AEER		4.60	3.83	3.49	3.22
	Star Rating		4.5	3.0	2.0	1.5
	New Star Rating Hot & Humid Mixed Cold		4.5	3.5	3.0	
			4.0	3.5	3.0	
			4.0	3.5	3	.0
	Running Current [Rated]	A	3.00	4.20	5.40	6.90
	In [Quie SPL Mid-Hi-		19 - 42	21 - 42	28 - 43	30 - 43
	Out [PV		47 (58)	49 (62)	50 (62)	52 (65)
	Air Volume (In) [C	Quiet- L/S	67 -	67 - 175 97 - 187 97 - 188		97 - 188
Heating	Capacity [Rated] kW		3.20	4.00	5.40	5.80
	Capacity [Min-Max] kW		1.00 - 4.20	1.30 - 5.10	1.30 - 6.30	1.40 - 7.50
	Total Input [Rate	d] kW	0.70	0.95	1.46	1.56
	Total Input [Min-Max] kW		0.23 - 1.17	0.21-1.33	0.26 -2.05	0.30 - 2.64
	СОР		4.57	4.21	3.71	3.72
	ACOP		4.55	4.20	3.70	3.71
	Star Rating		4.5	4.0	3.0	2.5
	New Star Rating Hot & Humid Mixed Cold		3.0 2.5			
			2.5			
			2.5		2.0	
	Running Current [Rated]	A	3.50	4.40	6.50	7.10
	In [Quie SPL SHi]	et- dB(A)	21 - 45	21 - 46	28 - 48	30 - 49
	Out [PV	VL] dB(A)	48 (61)	50 (63)	51 (64)	52 (65)
	Air Volume (In) [0 SHi]	Quiet- L/S	67 - 198	67 - 212	92 - 220	107 - 243
Piping	Diameter [Gas/L	iquid] mm	ø9.52/ø6.35			
	Max. Length/Hei	ght m		20/12		30/15
Indoor Unit	Input (Cooling/ Heating) [Rated]	w	20/26	20/30	23/33	23/43
	Dimensions [HxWxD] mm		299 × 885 × 195			
	Weight kg		11.5			
Outdoor Unit	Dimensions [HxV	VxD] mm		550 × 800 × 285		714 × 800 × 285
	Weight	kg	31.0	34.0	35.0	40.0
	Breaker Size A		1	0	12	16
uaranteed		g °C	-10 ~ 46			
Operating Range [Outdoor] Heating		°C	-15 ~ 24			







^{*1} Optional Wi-Fi adapter required per unit.

Requires an internet connection and the App downloaded on your smartphone or tablet with the latest operating system available.
*2 To use Amazon Alexa to control your air conditioner you will need an Amazon Alexa Echo device.
*3 To use Google Assistant to control your air conditioner you will need a Google Home Smart speaker.



MitsubishiElectric.com.au